



MX 3200

Safety stitch machine

MX 5200

Overlock



PEGASUS®

MXneo SERIES

Intelligently integrated



Compact & Powerful!

Devices included



Thread chain cutter

A thread chain is cut as soon as it is sucked up by air suction. There is no need to cut the thread chain using scissors. Therefore, these devices dramatically increase operational efficiency.



Presser foot lift

Pressing the treadle with your heel raises the presser foot. This device is easy to use, thus decreasing operator fatigue and increasing productivity.



Automatic tape cutter

The cutter knife automatically descends to cut a tape and/or thread chain when the sensor detects the edge of the fabric. Since the length of tape or thread chain that remains after a cut can be adjusted by stitch counting as desired, no skilled operator is needed.



Pneumatic lint collector

This pneumatic device strongly sucks up cutting waste and fine dust generated during sewing, providing clean and comfortable working conditions.



MX 3200 Safety stitch machine

MX 5200 Overlock

MXneo SERIES

Model	No. of needles	No. of threads	Needle space (mm)	Overedge width (mm)	Max.stitch length (mm)	Diff.feed ratio	Presser foot lift (mm)	Needles	Max speed (sti/min)
MX3216(-A)-02/223	2	5	3	4	1.6	1: 0.7~2.0	5.0	#11 DCX27	7500
MX3216(-A)-03/333	2	5	3	4	1.6	1: 0.7~2.0	5.5	#14 DCX27	7000
			5	5					
MX3244(-A)-03/333	3	6	3	2+4	1.6	1: 0.7~2.0	5.5	#11 DCX27	7000
MX3216(-A)-A04/435	2	5	5	6	2.5	1: 0.8~1.5	7.0	#21 DCX27	6500
MX3216N-A-01/232	2	5	3	4	1.25	1: 0.4~1.5	5.0	#11 DCX27	7500

Model	No. of needles	No. of threads	Needle space (mm)	Overedge width (mm)	Max.stitch length (mm)	Diff.feed ratio	Presser foot lift (mm)	Needles	Max speed (sti/min)
MX5204(-A)-02/233	1	3	-	4	1.6	1: 0.7~2.0	5.0	#9 DCX27	8000
MX5214(-A)-03/333	2	4	2	3	1.6	1: 0.7~2.0	5.5	#9 DCX27	7500
			2	4					
			2	5					
MX5214(-A)-M03/333	2	4	2	4	1.6	1: 0.7~2.0	5.5	#9 DCX27	7500
			2	5					
MX5204(-A)-32R2/223L	1	3	-	1.5	1.6	1: 0.7~2.0	5.0	#11 DCX27	8000
MX5214(-A)-53/633	2	4	2	4	1.6	1: 0.7~2.0	6.0	#9 DCX27	6500
			2	5					
			2	7					
MX5214(-A)-M53/333	2	4	2	4	1.6	1: 0.7~2.4	5.5	#9 DCX27	7500
			2	5					
MX5214(-A)-54/443	2	4	2	4	1.6	1: 1.1~3.8	7.0	#11 DCX27	6500
MX5214N-A-01/283	2	4	2	4	1.6	1: 0.4~1.5	5.0	#9 DCX27	8000

PEGASUS CO., LTD.

5-7-2 Sagisu Fukushima-ku,
Osaka 553-0002 Japan
TEL : +81-6-6458-4739
FAX : +81-6-6454-8785



<https://www.pegasus.co.jp/>

URL:<https://www.pegasus.co.jp>



※The specification and/or appearance for equipment described in this catalog are subject to change because of modification without previous notice.

© 2023 PEGASUS CO., LTD. NO.103183 Produced September 2023.