



PEGASUS

W2600

series

Extra high speed,
2013-needle, cylinder bed,
Interlock stitch machines




Offers speed and safety

Achieved the maximum machine speed at 7,000 rpm.

The machine runs fastest in the world a long distance, such as hemming bottoms of T-shirts and similar garments, thus increasing production.

New design that ensures safety for the operator

The driving parts conventionally located on the front of the arm have been totally removed. Your operators work feeling at ease with the resultant increase in production and quality.



W2600 Subclasses

Seam	Type of machine	Model	No. of needles	No. of threads	Needle space (mm)	Max. machine speed (rpm)	Remarks
Versatile machine							
1 2 3	Versatile machine for various applications, such as plain seaming, covering, hemming	W2664-01	2-3	4-5	3.2,4.0,4.8	6,500	
4 5 6		W2664S-01			5.6,6.4	7,000	
Binding tape							
7 8	For binding tape on leg openings of briefs, neck openings of T-shirts or underwear, etc.	W2664-02	2-3	4-5	3.2,4.0,4.8 5.6,6.4	6,500	
Covering							
3 4	For covering overlock seams on T-shirts or sweat shirts	W2664-03F	2-3	4-5	4.0,4.8,5.6	6,500	Flattening out overlock seams
9 10		W2664-03G			6.5		Folding over overlock seams
Attaching lace/elastic lace							
11 12	For attaching lace and/or elastic lace to women's underwear and similar garments	W2664-05	2-3	4-5	3.2,4.0,5.6 6.4	6,000	With fabric trimmer device
Hemming							
5 6	For hemming flat and tubular goods, such as T-shirts, polo shirts and similar garments	W2664-08	2-3	4-5	4.0,4.8,5.6,6.4	6,500	
		W2664S-08			7,000		
		W2664-35			4.8,5.6,6.4	6,000	With fabric trimmer device
Attaching flat elastic							
13 14	For attaching flat elastic to tubular goods, such as the waists of briefs, etc.	W2664H-33	3	5	5.6,6.4	5,000	With fabric trimmer device, rear puller device
Inserting elastic							
15 16	For inserting elastic into tubular goods, such as sweat pants, nightwear, etc.	W2664-34	2-3	4-5	4.8,5.6,6.4	6,000	

The maximum machine speed in this table is a value for reference with a standard stroke of the needle bar. Detailed adjustments may be required according to the sewing conditions.



ety.



Specifications

- No. of needles 2 ~ 3 needles
- No. of threads 3 ~ 5 threads
- Needle space (mm) 2-needle machines (3.2, 4.0, 4.8, 5.6, 6.4)*
3-needle machines (5.6, 6.4)
- Main feed dog's movement amount (mm) Max. 4.5
- Differential feed ratio 1:0.6 - 1:1.1/1:0.9 - 1:1.8
- Presser foot lift (mm) Max. 7.0**
- Machine speed (rpm) Max. 7,000**

*Remove the middle needle from a 3-needle machine, if you use the machine as a 2-needle machine with a needle space of 5.6mm and 6.4mm.

**Depends on sewing conditions.



PEGASUS CO., LTD.

5-7-2 Sagisu Fukushima-ku, Osaka 553-0002 Japan
TEL : +81-6-6458-4739 FAX : +81-6-6454-8785



Specifications and appearance are subjected to changes without notice.
Read the instruction manual before operating the machine to ensure safe usage.
Photos for illustration purpose. They may not represent actual operating conditions and/or displayed optional parts.

